

Download Certificates

GREENGUARD Certification
GREENGUARD Gold Certification

Caimi Brevetti S.p.A.

Product Website:

http://www.caimi.com/snowsound/en/prodotti/

Link to this page

Certification Mark(s):





Caimi Brevetti S.p.A. / CORISTA

GREENGUARD Certification

Standard: UL 2818 - 2013 Standard for Chemical Emissions for

Building Materials, Finishes and Furnishings

Number: 69754-410

Certification Status: Certified

Certification Period(s) 8/2015 - 7/2016

GREENGUARD Gold Certification

Standard: UL 2818 -2013 Gold Standard for Chemical Emissions for

Building Materials, Finishes and Furnishings

Number: 69754-420

Certification Status: Certified

Certification Period(s) 8/2015 - 7/2016

Manufacturer's Description:

The patented CORISTA sound-absorbing panel uses Snowsound® technology and was designed by partnering with expert sound engineers and musicians of international repute, in a view to understand and meet their needs for acoustics, senses, emotions and practical use. Snowsound® technology sound-absorbing panels are made entirely of polyester with a variable density which allows a selective absorption of different sound frequencies. The panel consists of an internal padding in polyester fiber with variable density, decreasing from the outside into the core of the panel, coated on both sides with Trevira CS® fabric, bonded firmly to the padding. Double-sided, both sides have a convex section and have the same characteristics. The panel features a rigid edge and has no frame, so it's 100% recyclable. Class of reaction to fire: Euroclass B-s2, d0. The panels were tested in a reverberation room according to UNI EN ISO 354 standards obtaining "Class A sound absorption" to UNI EN ISO 11654 standards. To simulate the influence of the seasons on indoor environments, Snowsound® technology panels are subjected to a cycle of extreme weather conditions according to ISO 9142 standards in a climate chamber at -20°C (-4°F) to +70°C (+158°F) and humidity up to 90%.

Sustainable Building Programs Credits & Codes: This Product Contributes To:

- Australian Green Star Education
 - IEQ Credit 8 : Flooring/Furniture
- Australian Green Star Office Interiors
 - IEQ Credit 11 : Furniture/Wall Systems
- LEED v4 Building Design & Construction
 - EQ Credit 1: Enhanced Indoor Air Quality
 Strategies Option 2 Additional Enhanced IAQ
 Strategies D
 - EQ Credit 2: Low-Emitting Materials
 - EQ Credit 4: Indoor Air Quality Assessment -

Option 2 Air Testing

- MR Credit 7: Furniture and Medical Furnishings -Healthcare Only - Option 2 & 3
- LEED v4 Homes
 - EQ Credit 2: Contaminant Control Option 4 Air Testing
- LEED v4 Interior Design & Construction
 - EQ Credit 1 Enhanced Indoor Air Quality
 Strategies-Option 2D
 - EQ Credit 2: Low-Emitting Materials
 - EQ Credit 4: Indoor Air Quality Assessment -

Option 2 Air Testing

CERTIFICATEOF COMPLIANCE



Caimi Brevetti S.p.A. CORISTA

Certificate Number

08/04/2015 - 07/20/2016

Certificate Period

69754-420

Certified Status

UL 2818 -2013 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2.

Commercial furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2014e Credit 7.6.1, 7.6.2, and 7.6.3. Panel based workstations are modeled in the open plan environment. Casegood systems are modeled in the private office environment. Products also determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.1-2010. Educational furniture is modeled in the classroom environment. Residential furniture is modeled in the residential bedroom environment.



GREENGUARD Gold Certification Criteria for Furniture and Mattresses

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC (A)	-	0.22	mg/m³
Formaldehyde	50-00-0	9 (7.3 ppb)	μg/m³
Total Aldehydes (B)	-	0.043	ppm
4-Phenylcyclohexene	4994-16-5	6.5	μg/m³
1-Methyl-2-pyrrolidinone (C)	872-50-4	160	μg/m³
Individual VOCs (D)	-	1/2 CREL or 1/100th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Based on the CA Prop 65 Maximum Allowable Dose Level for inhalation of 3,200 µg/day and an inhalation rate of 20 m³/day.

⁽D) Allowable levels for chemicals not listed are derived from the lower of 1/2 the California Office of Environmental Health Hazard Assessment (OEHHA) Chronic Reference Exposure Level (CREL) as required per the CDPH/EHLB/Standard Method v1.1 and BIFMA level credit 7.6.2 and 1/100th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).

CERTIFICATEOF COMPLIANCE



Caimi Brevetti S.p.A. CORISTA

Certificate Number

08/04/2015 - 07/20/2016

Certificate Period

Certified

69754-410

Status

UL 2818 - 2013 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Office furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2014e Credit 7.6.1. Panel based workstations are modeled in the open plan environment. Casegood systems are modeled in the private office environment. Residential furniture is modeled in a residential bedroom environment.



GREENGUARD Certification Criteria for Furniture and Mattresses

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.50	mg/m³
Formaldehyde	50-00-0	61.3 (50 ppb)	μg/m³
Total Aldehydes (B)	-	0.10	ppm
4-Phenylcyclohexene	4994-16-5	6.5	μg/m³
Individual VOCs (C)	-	1/10th TLV	-

 $[\]text{(A)} \quad \text{Defined to be the total response of measured VOCs falling within the C}_6 - C_{16} \, \text{range, with responses calibrated to a toluene surrogate}.$



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).

Deze informatie is afkomstig van de website van Zero-Z design.

Voor vragen, toelichting en meer informatie kunt u contact opnemen met:

Zero-Z design

Jasmijnstraat 6a

3732 EC De Bilt

T +31 (0)30 2201297

F +31 (0)30 2210692

E info@zero-z-design.nl

W www.zero-z-design.nl

